



GP COLOR

Revision: 01/01/2018

Page 1 of 2

Technical Data:

Consistency	Paste
Curing System	Moisture Cure
Skin formation (20°C/65% R.H.)	Ca 25-30 min.
Shrinkage (DIN 52451)	≤ 15%
Specific Gravity (DIN 53479B)	1.48g/mL
Temperature Resistance	-20°C to +80°C
Maximum allowed Distortion	± 15%
Maximum gap filling capacity	6mm
Joints with movements up to	± 15%

Product:

General Purpose Color is moisture evaporating construction grade sealant.

Characteristics:

- Very good adhesion on porous surfaces, aluminium & wood
- Maximum gap filling capacity 6mm
- Movement capability ±15%
- Colourfast and waterproof after curing
- Can be painted over after curing in interior and exterior applications
- Good UV resistance

Applications:

- Joints with movements up to ± 15%
- Connection joints in the building industry
- Joints between windowsills, between skirting-board and floor, between brickwork, etc

Packaging:

Colour: white, grey, brown, black
Packaging: cartridge 260ml

Shelf life and storage:

12 month from date of manufacturing in unopened packaging stored in a cool and dry place at recommended temperatures between +5°C and +35°. Protect against frost.

Not suitable for:

- Natural stone
- Structural glazing
- Mirrors
- Glass to glass
- Automotive applications

Joint Size:

Maximum gap filling capacity: 6mm

Applying the sealant:

Method: Apply the sealant by means of a handheld or pneumatic caulking gun. Smoothen the sealant with a filling-knife

Application temperature: +5°C to +35°C, do not apply when rain or frost are imminent

Clean: Uncured GP Color can be removed from tools with water. Cured sealant must be removed mechanically

Finishing: with water

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.

McCoy Soudal Sealants Adhesives & Foams Pvt. Ltd.

McCoy Corporate Tower, C-55, Okhla Industrial Area, Phase-1, New Delhi - 110020 (INDIA)

Tel.: +91 11 40623344 (100 lines) | Fax: +91 11 40623355

Website: www.mccoysoudal.com | Email: info@mccoysoudal.com

1800-121-6569 (Toll Free)



GP COLOR

Revision: 01/01/2018

Page 2 of 2

Health- and safety recommendations:

Apply the usual industrial hygiene
Consult the label for more information

Remarks:

- Do not use in applications with continuous water immersion
- Do not apply when rain or frost is imminent
- The paint should be sufficiently elastic to be applied on a plasto-elastic sealant. A preliminary test is recommended
- GP Color can be painted over with most paints

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.

McCoy Soudal Sealants Adhesives & Foams Pvt. Ltd.

McCoy Corporate Tower, C-55, Okhla Industrial Area, Phase-1, New Delhi - 110020 (INDIA)

Tel.: +91 11 40623344 (100 lines) | Fax: +91 11 40623355

Website: www.mccoysoudal.com | Email: info@mccoysoudal.com

1800-121-6569 (Toll Free)